



PRODUCT INFORMATION

November 2013

30090 Mobile Waste Oil Extractor

The 30090 mobile waste oil extractor available from Alemlube easily and efficiently extracts waste oil from engine crankcases, transmissions and differentials. With a holding tank capacity of 80 litres the 30090 has been designed to safely transfer and capture waste oil which can then be emptied from the machine with the aid of air pressure. The 30090 transfers waste oil at a rate of 6.5 litres per minute and the air pressure for the vacuum operates at 120psi (8bar) and low noise level. Inclusive of a safety valve to avoid over pressurisation, a large tray for tools, washers, filters etc., two reinforced 4" castors and two 6" reinforced reels the 30090 mobile waste oil extractor from Alemlube is covered by a twelve month warranty and is sure to provide years of reliable service.



PRODUCT SPECIFICATIONS, FEATURES AND BENEFITS

Extracts and captures waste oil from crankcases, transmissions and differentials

Holding tank capacity of 80L

Chamber depressurisation time of 25 seconds

Suction speed of 6.5 L/min

Suction hose specification of 1/2" x 2000mm

Draining hose length of 1" x 2000mm

Draining pressure of 14psi (1bar)

1/4" air inlet connection

12 month warranty

Also available 30091 as above with clear inspection chamber

ORDERING INFORMATION

30090
Mobile Waste Oil Extractor

