

NEW PRODUCT



INFORMATION

505224N

Samoa 15m x 19mm ID Spring Rewind Hose Reel



May 2023

The Samoa 505224N spring rewind hose reel is aimed directly at the mining, construction and general industries.

This 505 Series double pedestal arm design hose reel reliably delivers low pressure air, oil, water, waste oil, diesel and can be put to work in vehicle workshops, field service units, lube trucks, construction and general industry.


The 505224N Samoa spring rewind hose reel incorporates the spool mounted on two permanently lubricated sealed ball bearings which reduce torque load on the power spring resulting in smooth operation and extreme durability.

Capable of being installed on a wall, ceiling, floor or tank the 505224N outlet guide can be positioned in any one of seven positions for optimum operation. This rigid and stable structured spring rewind hose reel can withstand the most demanding applications known.

SPECIFICATIONS, FEATURES AND BENEFITS

- Heavy duty full metal double pedestal construction
- Hose capacity: 15m x 19mm ID
- 1,520psi (105bar) hose pressure rating
- 3/4" (f) inlet thread
- 3/4" (f) outlet thread
- True 3/4" full flow shaft & ports
- Seven position outlet arm
- Full port nickel protected steel shaft
- Large effective radial latching area for easy operation
- Fatigue resistance steel spring for longevity
- Manufactured using 4mm gauge steel
- Weight of 38kg
- Epoxy coated for increased wear resistance
- Width: 248mm

	mm (in)
A	594 (23 3/8")
B	248 (9 7/8")
C	Ø551 (21 3/4")
D	560 (22 1/16")
E	Ø10 (3/8")
F	130 (5 1/8")
G	220 (8 2/3")



Also available:

- 505924 Standard Bare Reel
- 505224SS Underground Coal Mining Reel
- 505924S Underground Coal Mining Bare Reel



www.alemlube.com.au

www.alemlube.co.nz

NSW/ACT (02) 9677 1555

QLD/PNG (07) 3204 9166

VIC/TAS (03) 8787 8288

WA (08) 9302 4199

SA/NT (08) 8241 7111

NZ (09) 447 1007